

JETFLOCK SOLVENT

Description Polyester flock material with paper backing, created for inkjet digital printing & cutting systems with solvent and eco solvent based inks. It features high covering power, brilliant color reproduction and easy workability.

Average film thickness before transfer: **450 micron**

Usage informations Due to the many different base materials available on the market, the following instructions are given as a guideline only :

Plotter settings (eg. with ROLAND VP-300)

Blade: **new at 50°**

Minimum cutting pressure: **120 gf**

Transfer setup

Temperature: **180 °C (360°F)**

Time: **15 seconds**

Pressure: **medium (3÷4 bar)**

Procedure

Print and cut the material

Let the print dry at least 12 hours before rolling, overlaying or heat transferring the material

Weed the exceeding material

Remove the print by hand

Cover with silicon treated paper or Teflon®

Heat apply

Remove the cover

Certifications The product is REACH approved

Suitable textiles Cotton, polyester and blends of these materials (not suited for treated and dye sublimation fabrics)

Washing instructions Wait **24h** after the heat transfer
60°C – inside out - Use neutral, non-aggressive and non-liquid laundry detergents
 Do not use bleach or other aggressive chemical agents.
 Dry clean: **no**
 Tumble dry: **yes**



Siser s.r.l.

N.B. All information given in this sheet are based on our experience.
 We always recommend performing a test before starting standard production.
 For best results we recommend to store the product away from direct sunlight.