

P.S. ELECTRIC

Description PU plotter cut heat seal material with adhesive polyester backing and bright colors. The material grants a good workability during the weeding and application phases and is highly wash-resistant. Recommended for overlaying applications. The material is certified Öko-Tex® Standard 100 Class I

Average film thickness before transfer: **90 micron**

Usage informations Due to the many different base materials available on the market, the following instructions are given as a guideline only :

Plotter settings (eg. with SUMMACUT D60 – ROLAND GX24)

Blade: **new at 50°**

Minimum cutting pressure: **60 gf**

Transfer setup

Temperature: **150 °C (300°F)**

Time: **15 seconds**

Pressure: **medium (3÷4 bar)**

Procedure

Mirror cut the material

Weed the exceeding material (for a quick and easier weeding, we suggest to place the cut material for a few seconds on a warm surface such as the plates, 60-70°C)

Place the material on the garment with its polyester backing

Heat apply

Remove the support warm or cold

Certifications

The product is REACH approved

The product is certified Öko-Tex® Standard 100 Class I



Suitable textiles

Cotton, polyester and blends of these materials (not suited for treated and dye sublimation fabrics)

Washing instructions

Wait **24h** after the heat transfer

60°C

Do not use bleach or other aggressive chemical agents.

Dry clean: **no**

Tumble dry: **yes**



Siser s.r.l.

N.B. All information given in this sheet are based on our experience.

We always recommend performing a test before starting standard production. For best results we recommend to store the product away from direct sunlight.